



CS-500 SERIES



Professional UHF Wireless Microphone system

Certifications : CE and RoHS /

The CS-500 Series conforms to standard **NBTC** | IEC 60950-1

CLEAR SOUND CS-500


UHF DUAL HANDHELD WIRELESS MICROPHONE

FEATURE

 783.3 TO
757.7 MHz

CH: 40
channels

 UP TO
50M

30Hz ~ 20kHz
 ±2dB

- UHF 748.3 ~ 757.7 MHz Frequency Range. (Brand for Thailand Regulation)
- Frequency Response 30Hz ~ 20kHz ±2dB
- Pre-Set 40CH (2*20CH) Selectable Frequencies.
- Unique digital pilot technology, no crosstalk disturbance even same frequency.
- An efficient battery energy design that allows the microphone to be used continuously for longer periods of time.
- IR Sync Downloading the Frequency from Receiver.
- The transmitter uses LCD display to indicate frequency and battery level and so on.
- Single-chip microphone amplifier, DSP-based audio processor with multi-frequency selection function.
- Up To 50 Meters Line-of-Sight Range.
- Ideal for large and small stages, Clubs Music Entertainment, Conference, Meeting, Training, Speeches and karaoke Etc.

Certifications : CE and RoHS

The SU-820D Series conforms to standard NBTC | IEC 60950-1

CLEAR SOUND CS-500

UHF DUAL HANDHELD WIRELESS MICROPHONE



CS-500DR : DUAL RECEIVER

- UHF 748.3 ~ 757.7 MHz
- Up to 9.5MHz bandwidth
- up to 40 Channels (2*20CH)



CS-500HT : HANDHELD TRANSMITTER

- Frequency Response 30Hz ~ 20kHz \pm 2dB
- Microphone Type Dynamic
- Polar Pattern Cardioid Directional
- Two transmission modes 40CH (2*20CH)
- Up To 50 Meters Line-of-Sight Range
- Battery Voltage 3V (2x1.5V AA Battery) approx. >5 hours

SPECIFICATIONS

SYSTEM

Carrier Frequency	UHF 748.3 ~ 757.7 MHz
Available Channels	40CH (2*20CH)
Bandwidth	9.5 MHz
Dynamic Range	96dB
Total Harmonic Distortion	<0.3%
Frequency Response	30Hz ~ 20kHz \pm 2dB
Audio Output Level	1 x 6.3mm, 2 x XLR balance output

CS-500DR : DUAL RECEIVER

Frequency Response	30Hz ~ 20kHz \pm 2dB
Power Supply	DC 12V 500mA
Consumption Power	<3watts
Signal/Noise Ratio	96dB
Receiving Sensitivity	-95dBm

CS-500HT : HANDHELD TRANSMITTER

Carrier Frequency	UHF 748.3 ~ 757.7MHz
Bandwidth	9.5 MHz
Frequency Response	30Hz ~ 20kHz \pm 2dB
Frequency Switch	IR SYNC
Microphone Type	Dynamic
Polar Pattern	Cardioid Directional
Output Power	10mW
Harmonic Radiation	<-50dBc
Battery Voltage	3V (2x1.5V AA Battery)
Battery Life	approx. >5 hours

CS-500 UHF DUAL HANDHELD WIRELESS MICROPHONE

Professional Music Entertainment, karaoke, Meeting, Training, Speeches and Etc.



SOUND VISION CO., LTD.

9 Chaiyaphruek Rd., Taling Chan, Taling Chan, Bangkok 10170 Thailand

Support : 02-433-9988

Email : info@soundvision.co.th

Line-at : @soundvision

www.soundvisionpro.com