

PSPM2 Series

6.35mm Jack male stereo to 2 x 6.35mm

Cable conductor $\Phi 4*8mm$ black Shell plating Black plated 2 lengths(meter): 1m, 2m

AUDIO CABLES



PHONE PLUGS 1/4" (6.35MM.)

Jack male mono

FEATURES

- Unique zinc alloy housing design, increased friction, more in line with humanized concept.
- Housing is available in black or nickel coating, gold-plated tip contact, more resistant to oxidation.
- Elastic PVC sleeve provides excellent cable protection.
- Compatible with cables of diameter up to 7mm.


80.9mm

SPECIFICATIONS

Material	
Shell	die-cast zinc alloy
Contact material	brass
Contact plating	nickel or gold plated
Sleeve	flexible PVC
Electrical & Mechanical	
Contact resistance	according to
	matching connector
Insulation resistance	>100MΩ
Dielectric Strength	300V dc
Life time	>1000 times

FEATURES

- Unique zinc alloy housing design, increased friction, more in line with humanized concept.
- Housing is available in black or nickel coating, gold-plated tip contact, more resistant to oxidation.
- Elastic PVC sleeve provides excellent cable protection, available in two colors, which can be used to distinguish "left" and "right" channels.
- Compatible with cables of diameter up to 7mm.



SPECIFICATIONS

Material	
Shell	die-cast zinc alloy
Contact material	brass
Contact	nickel or gold plated
Sleeve	flexible PVC
Electrical&Mechanical	
Contact resistance	according to
	matching connector
Insulation resistance	≥ 1GΩ
Dielectric Strength	500V dc
Life time	>1000 times

ORDER INFORMATION

PSPM2-A01M 1 METERS
PSPM2-A02M 2 METERS

Verification of compliance : RoHS