



SOUNDVISION KBD2020 IP a network (IP Based) PTZ camera controller, is fully compatible with many PTZ camera coding protocols from the main manufacturers, supporting ONVIF, VISCA, Serial port VISCA, PELCO-D/P protocols and etc. This compact camera controller features a high-quality joystick that allows variable speed control, as well as fast camera switching, quick-set camera parameters and so on. The industrial-grade blue screen LCD module has excellent display effect with fine and clear characters.

Feature

- Supporting ONVIF, VISCA, Serial port VISCA, PELCO-D/P protocols and etc.
- RJ45, RS422, RS232 control interfaces; Control up to 255 Cameras.
- Unique control code learning function allows customers to modify the control code instructions
- Any device on the RS485 bus can be individually configured with different protocols and baud rates.
- All camera parameters can be set through the button operation.
- Metal shell, silicone key design.
- LCD display, keypad sound prompt, real-time display decoder and matrix working status.
- 4D joystick allows variable speed control to cameras
- Maximum communication distance: 1200M (0.5MM) Twisted-Pair Cable

Specifications

| | |
|-----------------------------|---|
| Port | Network: RJ45. Serial Port: RS422, RS232 |
| Protocol | Network: ONVIF, VISCA Serial Port: VISCA, PELCO-D, PELCO-P |
| Communication BPS | 2400bps, 4800bps, 9600bps, 19200bps, 38400, 115200 |
| Interface | 5PIN, RS232, RJ45 |
| Joystick | 4D (up, down, left, right, zoom, lock) |
| Display | LCD Blue Screen |
| Prompt tone | ON/OFF |
| Power Supply | DC12V±10% |
| Power Consumption | 0.6W MAX |
| Working Temperature | -10°C ~ 50°C |
| Storage Temperature | -20°C ~ 70°C |
| Environment humidity | ≤90%RH (nondew) |
| Dimensions (WxHxL) | 179.3*109.9*320 mm |
| Upgrade | WEB Upgrading |