



SVS-62W

6.5-INCH TWO-WAY SURFACE-MOUNT SPEAKER



The **SVS-62W** is a new Passive two-way surface-mount speaker ideal for indoor and outdoor applications requiring high-quality sound. Model SVS-62W designed for a wide range of commercial audio applications including retail shops, hotels, shopping malls, restaurants, conference- rooms, bars and health clubs.

Model SVS-62W are available in black ,Transformer Taps 70V: 40W, 20W, 10W, 5W | 100V: 80W, 40W, 20W, 10W available for constant voltage systems.

SVS-62W supports applications multiple:

- Meeting Room.
- Conference Room.
- Training Rooms.
- Hotels.
- Health clubs.
- Retail shops.
- Shopping malls & Plaza.
- Restaurant & Bar.

Feature

- Passive Two-Way Full-range Loudspeaker.
- Elegant design.
- High-quality sound.
- Indoor and outdoor applications.
- All-weather versatility IP54*
- High sensitivity.
- Transformer Taps 70V, 100V
- 6.5-inch LF transducer 60Watts rms
- 1-inch HF transducer 20Watts rms
- Power Handling 160Watts
- Frequency Response 50Hz ~ 20kHz
- Coverage H 90° x V 60°

***SVS-62WP**



- Passive Two-Way Full-range Loudspeaker.
- All-weather versatility IP54*
- High-quality sound.
- High sensitivity.
- 6.5-inch LF transducer 60Watts rms
- 1-inch HF transducer 20Watts rms
- Transformer Taps 70V, 100V.
- Power Handling 160Watts.
- Frequency Response 50Hz ~ 20kHz
- Coverage H 90° x V 60°

Specifications

All-weather versatility	IP54*
Color	Black
Input Connections	Euroblock
Speaker Type	Full-range, Mid-High, Two-Way
Transformer Taps	70V : 40W, 20W, 10W, 5W 100V : 80W, 40W, 20W, 10W 8Ω Bypass
Frequency Response	65Hz ~ 20kHz (-3dB) 50Hz ~ 20kHz (-10dB)
Sensitivity 1W/1m	93dB
Max. SPL/1m (calc)	118dB
Coverage (Nominal -6 dB) H	90° (±45°)
Coverage (Nominal -6 dB) V	60° (±30°)
System Power Handling	160W Max. / 80W continuous
LF Transducer	6.5-inch Waterproof Paper Cone (Glass fiber cone technology)
HF Transducer	1-inch (Silk dome)
Nominal Impedance (Passive)	8Ω
Indoor / Outdoor	Yes
Material	Engineering-plastics (ABS)
Dimensions (H x W x D mm)	330 x 196 x 300mm
Weight	10.5 Kg/ pair , 5 Kg / Single